

Virtual Server Information

Supported Versions	Last Updated
1.2.00 & higher json output 1.14.00 & higher	2013/05/04

Action	vserver-info
Method	GET, POST
Variables	<pre>vserverid [id of virtual server] reboot [true/false] (only required for Xen PV) if not specified default is false rdtype [json] For json output specify json or for default output leave blank. This variable is optional</pre>

Example
Output

XML

Success:

```
<status>success</status>
<statusmsg></statusmsg>
<vserverid>[vserverid]</vserverid>
<ctid-xid>[ctid or xen id]</ctid-xid>
<clientid>[clientid]</clientid>
<ipaddress>[main ipaddress]</ipaddress>
<hostname>[hostname]</hostname>
<template>[template]</template>
<hdd>[diskspace]</hdd>
<memory>[memory]</memory>
<swap-burst>[swp or burst memory]</swap-burst>
<type>[openvz/xen/xenhvm]</type>
<cpus>[1]</cpus>
<mac>[mac address]</mac>
```

Error:

```
<status>error</status>
<statusmsg>ERROR MESSAGE</statusmsg>
```

JSON

Success:

```
{
  "status": "success",
  "statusmsg": "",
  "vserverid": "[vserverid]",
  "ctid-xid": "[ctid or xen id]",
  "clientid": "[clientid]",
  "ipaddress": "[main ipaddress]",
  "hostname": "[hostname]",
  "template": "[template]",
  "hdd": "[diskspace]",
  "memory": "[memory]",
  "swap-burst": "[swp or burst memory]",
  "type": "[openvz/xen/xenhvm]",
  "cpus": "[1]",
  "mac": "[mac address]"
}
```

Error:

```
{ "status": "error", "statusmsg": "ERROR MESSAGE" }
```