

# List Virtual Servers

Supported Versions	Last Updated
1.2.00 & higher json output 1.14.00 & higher	2013/04/29

Action	<code>node-virtualservers</code>
Method	<code>GET, POST</code>
Variables	<pre>nodeid      [id of node] rdtype      [json] For json output specify json or for default output leave blank. This variable is optional</pre>
Example Output	<p><b>XML</b></p> <p><b>Success:</b></p> <pre>&lt;virtualservers&gt; &lt;virtualserver&gt; &lt;vserverid&gt;[vserverid]&lt;/vserverid&gt; &lt;ctid-xid&gt;[ctid or xen id]&lt;/ctid-xid&gt; &lt;clientid&gt;[clientid]&lt;/clientid&gt; &lt;ipaddress&gt;[main ipaddress]&lt;/ipaddress&gt; &lt;hostname&gt;[hostname]&lt;/hostname&gt; &lt;template&gt;[template]&lt;/template&gt; &lt;hdd&gt;[diskspace]&lt;/hdd&gt; &lt;memory&gt;[memory]&lt;/memory&gt; &lt;swap-burst&gt;[swp or burst memory]&lt;/swap-burst&gt; &lt;type&gt;[openvz/xen/xenhvm]&lt;/type&gt; &lt;mac&gt;[mac address]&lt;/mac&gt; &lt;/virtualserver&gt; &lt;/virtualservers&gt;</pre> <p><b>Error:</b></p> <pre>&lt;status&gt;error&lt;/status&gt; &lt;statusmsg&gt;ERROR MESSAGE&lt;/statusmsg&gt;</pre> <p><b>JSON</b></p> <p><b>Success:</b></p>

```
{
  "status": "success",
  "statusmsg": "",
  "virtualservers": [
    {
      "vserverid": "171",
      "ctid-xid": "vm108",
      "clientid": "1",
      "ipaddress": "95.45.23.7",
      "hostname": "test574.soluslabs.net",
      "template": "centos-5-x86_64",
      "hdd": "10737418240",
      "memory": "2147483648",
      "swap-burst": "1073741824",
      "type": "xen",
      "mac": "00:16:3e:73:15:b8"
    },
    {
      "vserverid": "168",
      "ctid-xid": "vm107",
      "clientid": "65",
      "ipaddress": "123.123.123.44",
      "hostname": "centos6.com",
      "template": "centos-6.0-x86_64-solus",
      "hdd": "10737418240",
      "memory": "1073741824",
      "swap-burst": "2147483648",
      "type": "xen",
      "mac": "00:16:3e:eb:41:5e"
    }
  ]
}
```

**Error:**

```
{"status": "error", "statusmsg": "ERROR MESSAGE"}
```